

DECLARATION OF PERFORMANCE

Product name: Bona SuperSport HD


Producer: Bona AB, Murmansgatan 130, Malmö, Sweden

Product type: 2-component waterborne wood floor lacquer formulated explicitly for professional use on wood sports floors

| | |
|---|---|
| Product type: | 2-component waterborne polyurethane lacquer |
| Solids content: | 32% |
| VOC: | Max 50 g/lit (including hardener) |
| Sheen (at 60°) | Gloss: 85% Matt: 20% (on glass) |
| Mixing ratio: | 1 part hardener to 1 litre SuperSport HD or 0.4 L hardener to 4,6 L SuperSport HD (≈8 vol%) |
| Pot life: | Max three hours at 20°C (shorter if warmer) |
| Drying time, until: | Recoating: 2-3 hours* Light use: 8 hours* Ready for play: 3 days* (see additional note under Application below) *under normal climate conditions, 20°C/60% R.H. |
| Application tools | Bona Microfleece Roller or Swivel Head Applicator. |
| Application rate: | 8-10 m ² /litre (100-120g/m ²) per coat |
| Safety | Coating: Unclassified Hardener: Classified (see Safety Data Sheet) |
| Cleaning: | Wipe tools free from residual material before cleaning with a minimum of water. Dried material can be removed with acetone. |
| Shelf life: | Lacquer: 1 year from the production date in the original unopened container. Hardener: 18 months from the production date in the original unopened container. |
| Storage/transport: | During storage and transport, the temperature must not fall below +5°C or exceed +30°C. |
| Disposal: | Waste and emptied containers should be handled by local regulations. |
| Pack size | 3 x 5 litres (36 boxes per pallet) |
| Certificates | |
| EMICODE | EC1 – Very low indoor emissions |
| FIBA certificate | DA, license no FC30-02 – approved for competition levels 1 and 2 |
| Resistance to the fire, according to 13501-1: | Bfl – s1 |
| Friction, according to EN 14904:2006 | 95 |

The information in this document and all other advice and recommendations we provide to help and assist the applicator is based on previous experience and extensive testing but does not claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturers and the provisions of relevant standards.

Malmö 2023-05-24



Thomas Hallberg

Director Product Management EMEA/AFAC

